

FICHA TECNICA SPLIT MURO CONVENCIONAL

ESPECIFICACIONES TECNICAS		UNIDADES	AA410-9	AA410-12	AA410-18	AA410-24	AA410-36
CAPACIDAD	FRIJO	btu/h	9000	12000	18000	24000	36000
	CALOR	btu/h	9500	12800	19000	24800	36600
POTENCIAL NOMINAL	FRIJO	W	820	1050	1620	2150	3800
	CALOR	W	720	910	1450	1900	3600
CORRIENTE NOMINAL	FRIJO	A	3,7	4,7	7,4	9,8	17,3
	CALOR	A	3,5	4,2	6,6	8,6	16,4
DIAM DE TUBERIA PULG.	LIQUIDA	pulgada	6.35-1/4"	6.35-1/4"	6.35-1/4"	6.35-1/4"	6.35-1/4"
	GAS	pulgada	9.52-3/8"	9.52-3/8"	12.7-1/2"	15.88-5/8"	15.88-3/4"
NIVEL DE DECIBEL (RUIDO): Dormi /Baja / Media/ Alto	IN	db (A)	18.4 / 27.7 31.6 / 36.2	19.2 / 28.4 32.8 / 37.0	21.7 / 30.5 34.30 / 39.70	23,5 / 34.9 39.1 / 43.6	25.1 / 45.3 47.1 / 49.80
	OUT	db (A)	51	52	55	55	58
CAUDAL		m3/h - HI	500	600	1000	1100	1550
APLICACION		area/mt2	12 - 20	15 - 25	26 - 36	40 - 50	55 - 70
REFRIGERANTE		**	R410A	R410A	R410A	R410A	R410A
COMPRESOR		**	GMCC (TOSHIBA)		GMCC (HITACHI)		HITACHI
DIMENSIONES CAJA Ancho / Fondo / Alto	IN	mm	770*355*285	870*370*295	920*370*295	1050*385*330	1250* 360* 253
	OUT	mm	780*345*550	780*345*550	920*395*605	940*420*750	975* 803* 390
CLASE ENERGETICA	FRIJO/CALOR	**	A/A	A/A	A/A	A/A	A/A

